

Model/Type	DC-646
Machine Type	Slitter/Cutter/Creaser
Paper Size	<u>Width</u> 210mm - 370mm <u>Length</u> 210mm - 670mm
Minimum output size	<u>Slit width</u> 48.0mm <u>Cut length</u> 50.0mm
Paper Type	Non coated, Coated, Laminated
Margin Slit	Width 3.2mm - 55.0mm from the paper side edge
Gutter Slit	Width 5mm - 15mm ※Gutter strips wider than 15mm are output on the exit tray.
Min Cut Length	<u>Lead edge cut</u> 3m <u>Gutter cut</u> 3.0 <u>Trail edge cut</u> 5.0mm
Paper Weight	110-350gsm
Slit - Cut - Crease	Up to 6 slits*, 30 cuts, 20 creases / document ※Max 8 slits by Optional Slitter Module OSM-02
Speed	30sheets/ min (A4SEF, 2cuts, 1 crease)
Input Tray Capacity	100mm
Stacker Capacity	140mm
PC Interface	USB 2.0 (A/B 4 pin) (Dulo original software : PC Controller)
Optional Module	Rotary Tool Module (RTM-03),Cross Rotary Tool module (CPM-03), Optional Slitter module (OSM-02), Optional PCB Kit (OPK-02)
Power	115VAC, 60Hz, 230VAC, 50/60Hz
Power Consumption	4.0 - 1.9A
Dimension	<u>In use</u> 2,310 (W) ×1,005 (D) ×1,110 (H) mm <u>In storage</u> 1,650 (W) ×1,005 (D) ×1,110 (H) mm
Weight	275kg