

Model/Type	Saddle Stitcher DBMS-F5/S5/T5
Machine type	Floor type
Paper type	<u>Fine quality paper</u> 64 to 157gsm <u>Art/Coated paper</u> 84.9 to 157gsm <u>Cover sheet</u> 300 gsm
Paper size	<u>Saddle stitching/Length</u> 210 to 610 mm <u>Width</u> 120 to 356 mm
Type of stitching	Saddle stitch
Maximum booklet thickness	6.0mm (1 Cover sheet + 29 inner sheets)
Maximum processing speed	<u>A4 size, within 10 sheets</u> 5,050sets/h <u>A3 size, within 10 sheets</u> 4,000sets/h
Thickness of Scoring/Folding	1.0mm (DBMS-S5 stack sub-sets on the buffer section)
Trimming width	1 to 25mm
Number of stitch	0 to 2 (3 or 4 stitch is available by optional equipment)
Detecting function	【DBMS-F5】 Paper jam, Cover open/close, Motor overload detection 【DBMS-S5】 Paper jam, No stitch detection, Stitcher dislocation detection, Cover open/close, Motor overload detection 【DBMS-T5】 Paper jam, Cover open/close, Knife stop position error, Motor overload detection
Rating and power consumption	【DBMS-S5】 200 to 240V, 50/60Hz, 3.0A, 510W 【DBMS-T5】 200 to 240V, 50/60Hz, 2.5A, 355W
Dimensions	【DBMS-F5】 1,433(W)×964(D)×914(H) mm 【DBMS-S5】 1,867(W)×1,142(D)×1,162(H) mm 【DBMS-T5】 716(W)×736(D)×1,181(H) mm 【Foot print】 <u>DSC-10/60iL x 2 towers + LUL-HM + DBMS-F5/S5/T5 + DKTS-200 + DBM-LSW2</u> 3,692(W)×4,238(D) mm
Weight	【DBMS-F5】 342kg 【DBMS-S5】 429kg 【DBMS-T5】 232kg
Options	4 STITCH KIT, 3 STITCH KIT, 6 PAGE COVER SHEET KIT, AIR KIT